

# SpeedStream®



## SpeedStream® DSL Modems, PPPoE Modems, and Routers

Broadband Connections via Ethernet or USB

4100, 4200

### Features

- > **Extensive Standards Support** – \*Compliance to ADSL2, ADSL2+ and RE-ADSL offer providers the ability to extend their reach to subscribers with greater performance.
- > **PPPoE Client** (PPPoE Modems and Routers only) – Embedded PPPoE client means no additional PC software is needed for broadband connectivity. An intuitive, web-based graphical user interface (GUI) makes installation effortless. Pre-configured Application Level Gateways (ALGs), support most popular games and applications, making remote interaction a snap.
- > **Corporate-Class Security** (Router only) – ICSA-compliant Stateful Inspection Firewall with Denial of Service (DoS) protection provides advanced security for Internet connections by preventing unauthorized access and shielding against outside attack. A choice of pre-defined or fully custom settings, make online security a reality - even without an IT staff.
- > **Cost Effective** – SpeedStream® 4100 and 4200 modems provide a cost-effective, full-featured DSL solution for subscribers. Their user-friendly installation and setup make technical support costs more manageable.

The 4100 Ethernet model works with any Ethernet equipped PC, regardless of operating system, while the 4200 Ethernet/USB combo model's dual interface is almost like two products for the price of one. Subscribers get the flexibility of connecting with convenient Ethernet or using effortless, plug-and-play USB, maximizing deployment options and subscriber value.

The SpeedStream® PPPoE Modem and Router's Web-configurable, embedded PPPoE client means service providers get easy deployment and activation while users get connected without loading software.

SpeedStream® DSL Routers have full-featured Web-based management and diagnostic tools, making support a snap. Their comprehensive routing features include: support for Network Address Port Translation (NAPT); Dynamic Host Configuration Protocol (DHCP); and Domain Name Server (DNS) relay.

\*Support for ADSL2, ADSL2+, and RE-ADSL standards with streamlined deployment and interface flexibility make SpeedStream® DSL Modems, PPPoE Modems, and Routers the perfect solution for residential CPE deployments.

**SIEMENS**

Global network of innovation



\*Available with certain firmware versions.

## Features and Benefits

- Web-based (HTTP) configuration of PPPoE parameters allows easy deployment (PPPoE Modems and Routers only)
- Configurable ICSA-compliant Stateful Inspection Firewall with Denial of Service (DoS) protection, provides secure communication and Internet access (Routers only)
- Concurrent NAT and NAT (Routers only)
- Available models provide the flexibility of connecting PCs via Ethernet or both USB and Ethernet
- 10/100 Ethernet provides full-rate LAN performance
- Up to 24 Mbps downstream and 1.5 Mbps upstream provides true broadband experience for subscribers
- Support for G.lite and full-rate ADSL, ADSL2, ADSL2+ and RE-ADSL ensure compatibility with most DSL networks
- 4200 model features simultaneous Ethernet and USB connectivity, allowing two PCs with discrete IP addresses or PPPoE clients to share a DSL line
- 4200 model is WHQL (Windows Hardware Quality Labs) certified, ensuring plug-and-play USB installation on any PC running Windows® 2000, Me, or XP

### 4100 Backpanel View



### 4200 Backpanel View



## Technical Specifications

### Bridging

- RFC 2684 (formerly 1483) Bridged Ethernet over ATM PVCs
- IEEE 802.1d transparent, learning bridge
- Dynamic learning of up to 255 addresses
- Spanning Tree Algorithm

### AAL and ATM Support

- Precise Peak Cell Rate traffic shaping on a per-VCC basis
- Up to 8 active VCCs across VPI 0-255,
- VCI 0-65535 address range
- ATM Forum UNI3.1/4.0 PVC
- ATM Traffic class: UBR, CBR, VBRnt, VBRrt
- OAM F4/F5

### Media Interface

- RJ-11 ADSL connection
- 10/100 Base-T RJ-45 Ethernet connection
- Auto-MDI/X
- Standard USB connection (4200 model only)

### Visual LED indicators

- Power
- ADSL
- Ethernet
- Internet (4100) or USB (4200)
- Activity

### Power

- External Supply-  
Input: 120VAC, 300mA, 60Hz  
Output: 12V/1A

### Standards Compliance

- IEEE 802.1d, 802.3, and 802.3u
- ADSL: G.DMT, G.LITE, ANSI T1.413 Issue 2, ADSL2, ADSL2+, RE-ADSL
- USB 1.1 (model 4200)

### Certifications

- FCC Part 15, Class B
- FCC Part 68
- CE certification
- UL listed
- CSA
- CS-03
- Industry Canada Mark
- WHQL (4200 model only with Windows® 2000, Me, or XP)

### Warranty

- One (1) year parts and labor for hardware
- Additional year available with product registration

### System Support/Minimum Requirements

- Ethernet Installation
- Ethernet NIC
- Operating system that supports TCP/IP over Ethernet

### USB Installation

(4200 model only)

- Windows® 98, 98SE, 2000, Me, or XP
- Pentium® processor 166MHz or faster
- 32 MB RAM
- 12 MB free disk space
- Free USB 1.1 or higher port

### PPPoE Modem Additions

#### Routing

- RFC 2516 Point-to-Point Protocol (PPP) over Ethernet
- DHCP server, DNS relay
- PPPoE Relay/Bridging

#### Management

- Web-based graphical user interface
- Instant operation from an operator-defined service profile

#### Security

- PAP (RFC 1334), CHAP (RFC 1994)
- Password Authentication

### Router Additions

#### Routing

- RFC 2364 Point-to-Point Protocol (PPP) over ATM PVCs
- RFC 2684 (formerly 1483) Bridged Ethernet encapsulation
- RFC 2225 (formerly 1577) Classical IP over ATM
- Network Address Translation (NAT)
- PAP or CHAP Auto-detection
- TCP/IP with RIP1 and RIP2 or static routing on the LAN and/or WAN

#### AAL and ATM Support

- Up to 8 active VCCs across VPI 0-225

#### Management

- Command Line Interface (CLI)
- Telnet
- SNMP v1

#### Security

- PAP (RFC 1334), CHAP (RFC 1994), MS-CHAP
- Access Control list
- Stateful Inspection Firewall with Denial of Service (DoS) protection
- Pre-configured firewall levels for ease of use with "Custom" level for advanced users
- Filter on source and/or destination IP address
- Filter on transport protocol and/or port number
- Firewall logging with Network Time Protocol support and Syslog support
- DMZ support and Firewall "Snooze" feature
- Graphical User Interface

#### Diagnostics

- Comprehensive hardware diagnostics
- Comprehensive Ethernet, ATM, and ADSL statistics

#### Media Interface

- Auto-MDI/X

# SIEMENS

Global network of innovation

Siemens Subscriber Networks, Inc.  
4849 Alpha Road  
Dallas, TX 75244  
(972) 852-1000  
Fax (972) 852-1001  
E-mail [info.ssn@siemens.com](mailto:info.ssn@siemens.com)  
[www.icn.siemens.com/subscriber](http://www.icn.siemens.com/subscriber)